

PFRD Service Migration to OAuth 2.0

Purpose


Effective June 25, 2022, FINRA is moving all application authentication from basic authentication to OAuth 2.0 to enhance security across its systems. In order to support this change, the previous endpoint will be replaced with a new “Version 2” of the PFRD service. This document was created to assist existing web service users who need to transition to the new service. (Users new to the service after June 25, 2022, will automatically use the new authentication method. We recommend that new users review the sample code in the XML Filing Guide rather than this transition document.)

Important note: The following guidance was successful using FINRA machines running on the internal FINRA network. You may need to make adjustments based on your specific systems. If you need assistance, please contact PFRDSupport@finra.org.

Flow Diagrams


Original Flow

In the original service flow, user credentials were directly passed to PFRD service in Soap XML which does authN/authZ and returns back appropriate results.



New Flow

In this flow, FIP service is called passing user credentials in basic auth, get the bearer token and then pass that to the PFRD service.



Updated Endpoints




Service	URL
FIP EWS	https://ews.fip.finra.org/fip/rest/ews/oauth2/access_token?grant_type=client_credentials
Path to New PFRD endpoint that supports OAuth 2.0	https://crd.finra.org/v2/PFRD/webservices/PFFormSubmissionService.svc

Implementation Details

To access the OAuth endpoint

- Download the WSDL for the new endpoint.
 - Example: <https://crd.finra.org/v2/PFRD/webservices/PFFormSubmissionService.svc?singleWSDL>
- Obtain an OAuth token from the FIP EWS service of appropriate environment using Basic Authentication with your username/password (e.g. mylogin/mypwd)
 - Example: https://ews.fip.finra.org/fip/rest/ews/oauth2/access_token?grant_type=client_credentials

Grab the *access_token* value from the returned json. Add the token in the header of your request. (Do not forget to add the Bearer prefix, followed by a space, followed by the token value as shown below)


Body   200 

Pretty

Raw

Preview

Visualize

JSON 

```
1 {
2   "access_token": "*AAJTSQACMDIABHR5cGUAA0pXV",
3   "scope": "any",
4   "token_type": "Bearer",
5   "expires_in": "43170"
6 }
```

Endpoint invocation

```
using (new OperationContextScope(service.InnerChannel))
{
    WebOperationContext.Current.OutgoingRequest
        .Headers.Add("Authorization", String.Format("Bearer
*AAJTSQACMDIABHR5cGUAA0pXVAACUzEAAjAx*....."));

    var result = service.Ping();
}
```

Sample binding setup for the PFRD V2 service:

Endpoint configuration

```
<bindings>
  <wsHttpBinding>
    <binding name="WSHttpBinding_PFFormSubmissionService">
      <security mode="Transport">
        <transport clientCredentialType="None" />
      </security>
    </binding>
  </wsHttpBinding>
</bindings>
```

Java Client

Sample build.gradle config task

Java Config

```
plugins {
    id 'java'
}

group 'org.example'
version '1.0-SNAPSHOT'

repositories {
    mavenCentral()
}

dependencies {
    compile "jakarta.xml.ws:jakarta.xml.ws-api:3.0.0"
    compile "com.sun.xml.ws:jaxws-rt:3.0.0"
    compile "com.sun.xml.ws:jaxws-ri:3.0.0"
    compile "com.konghq:unirest-java:3.11.09"
```

```

        testCompile group: 'junit', name: 'junit', version: '4.12'
        runtime 'com.sun.xml.ws:jaxws-tools:3.0.0'
    }

    task wsImport(type: JavaExec) {
        classpath sourceSets.main.runtimeClasspath
        main = "com.sun.tools.ws.WsImport"
        args "-target", "2.2",
            "-s", "src/main/java",
            "-keep",
            "-Xnocompile",
            "-encoding", "UTF-8",
            "src/main/resources/PFFormSubmissionService.xml"
    }
}

```

Java Client

```

import jakarta.xml.ws.BindingProvider;
import jakarta.xml.ws.handler.Handler;
import jakarta.xml.ws.handler.MessageContext;
import jakarta.xml.ws.soap.AddressingFeature;
import kong.unirest.HttpResponse;
import kong.unirest.Unirest;
import org.finra.crd.pfrd.PFFormSubmissionService;
import org.finra.crd.pfrd.PFFormSubmissionServiceImpl;

import javax.xml.namespace.QName;
import java.util.Arrays;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

public class Startup {

    public static class FipResponse {
        public String access_token;
        public String expires_in;
        public String token_type;
    }
}

```

```

    public String scope;
}

//1. Production URL for FIP token service
final static String tokenServiceUrl =
"https://ews.fip.finra.org/fip/rest/ews/oauth2/access_token?grant_type=client_credentials";
//2. Production URL for the PFRD service
final static String pfrdServiceUrl =
"https://crd.finra.org/v2/PFRD/WebServices/PFFormSubmissionService.svc";

public static void main(String[] args) {

    //Instantiate the service
    var service = new PFFormSubmissionServiceImpl();

    //NOTE -----
    // The PFFormSubmissionService class is generated by the WsImport tool. You can either
generate it at the command line
    // or define a gradle task like in the build.gradle configuration file above (task wsImport)
    //
    // The endpoint name @WebEndpoint(name = "WSHttpBinding_PFFormSubmissionService") is also
generated. You can find it
    // in your generated files : PFFormSubmissionServiceImpl.java
    //-----

    //get the port name and make sure to enable WS-A addressing
    // the QName for the port name is generated by the WsImport task.
    PFFormSubmissionService port =
        service.getPort(new QName("http://crd.finra.org/PFRD",
"WSHttpBinding_PFFormSubmissionService"),
            PFFormSubmissionService.class,
            new AddressingFeature(true, true)); //Important Note: this parameter enables WS_A
addressing mode

    BindingProvider bp = (BindingProvider)port;

    //1. Set up the endpoint address here
    bp.getRequestContext().put(BindingProvider.ENDPOINT_ADDRESS_PROPERTY, pfrdServiceUrl);

    //Set up the Oauth header

```

```

        Map<String, List<String>> requestHeaders = new HashMap<>();
        //Get the OAuth token for your specific username/password
        requestHeaders.put("Authorization", Arrays.asList(getOAuthTokenFor("userName", "password",
tokenServiceUrl)));
        bp.getRequestContext().put(MessageContext.HTTP_REQUEST_HEADERS, requestHeaders);

        //call the service
        Boolean ping = port.ping();
        System.out.printf("Result: %s", ping );
    }

    private static String getOAuthTokenFor(String userName, String password, String tokenServiceUrl){

        HttpResponse<FipResponse> response = Unirest.post(tokenServiceUrl)
            .basicAuth(userName, password).asObject(FipResponse.class);

        if (response.isSuccess()) {
            FipResponse fipResponse = response.getBody();
            return String.format("Bearer %s", fipResponse.access_token);
        }
        throw new RuntimeException("Unable to get the OAuth token");
    }
}

```


.NET Client

The .NET configuration is generated automatically by adding a service reference in your .NET project. Here is an example generated for the QA environment.

For the Production environment, please replace the endpoint's address.

.NET Configuration

```
<?xml version="1.0" encoding="utf-8"?>
<configuration>
  <startup>
    <supportedRuntime version="v4.0" sku=".NETFramework,Version=v4.7.2" />
  </startup>
  <system.serviceModel>

    <bindings>
      <wsHttpBinding>
        <binding name="WSHttpBinding_PFFormSubmissionService">
          <security mode="Transport">
            <transport clientCredentialType="None" />
          </security>
        </binding>
      </wsHttpBinding>
    </bindings>
    <client>
      <endpoint address="https://crd-
gaint1.qa.finra.org/v2/PFRD/WebServices/PFFormSubmissionService.svc"
                binding="wsHttpBinding"
                bindingConfiguration="WSHttpBinding_PFFormSubmissionService"
                contract="PFService.PFFormSubmissionService"
                name="WSHttpBinding_PFFormSubmissionService" />
    </client>
  </system.serviceModel>
</runtime>
<assemblyBinding xmlns="urn:schemas-microsoft-com:asm.v1">
  <dependentAssembly>
    <assemblyIdentity name="System.Runtime.CompilerServices.Unsafe" publicKeyToken="b03f5f7f11d50a3a"
culture="neutral" />
  </dependentAssembly>
</assemblyBinding>
</configuration>
```

```

        <bindingRedirect oldVersion="0.0.0.0-5.0.0.0" newVersion="5.0.0.0" />
    </dependentAssembly>
</assemblyBinding>
</runtime>
</configuration>

```

.NET Client

Please note that we used the RestClient library to call the FIP endpoint, but it can be any REST library of your choice.

The important thing to remember is that the FIP call to get an OAuth token uses Basic Authentication and it is a POST call.

```

using RestSharp;
using RestSharp.Authenticators;
using System;
using System.IO;
using System.Net;
using System.Reflection;
using System.ServiceModel;
using System.ServiceModel.Web;
using System.Text.Json.Serialization;

namespace PFClient
{
    class Program
    {
        //FIP QA Url (To be replaced with prod URL)
        public static string fipUrl = "https://ews-
qaint.fip.qa.finra.org/fip/rest/ews/oauth2/access_token?grant_type=client_credentials";
        //FIP JSON Response structure
        private class FipResponse
        {
            [JsonPropertyName("access_token")]
            public String AccessToken { get; set; }
            [JsonPropertyName("expires_in")]
            public String Expiration { get; set; }
        }
    }
}

```

```

static void Main(string[] args)
{
    //Handle SSL cert if needed
    ServicePointManager.ServerCertificateValidationCallback += (sender, cert, chain,
sslPolicyErrors) => {
        return true;
    };

    //The settings for the service have been generated in app.config (or PFClient.exe.config)
    var service = new PFService.PFFormSubmissionServiceClient();
    var userName = "JOINT877";
    var password = "****";
    //call the EWS oAuth endpoint to obtain token
    FipResponse fipResponse = GetFipToken(userName, password);
    //Access the context scope in order to set the authorization header
    using (new OperationContextScope(service.InnerChannel))
    {
        //prepare the Auth header
        var authHeader = String.Format("Bearer {0}", fipResponse.AccessToken);
        //set the header for the outgoing request
        WebOperationContext.Current.OutgoingRequest.Headers.Add("Authorization", authHeader);

        //Test call to Ping
        var result = service.Ping();

        //Test call to UploadFiling
        using(var stream =
Assembly.GetExecutingAssembly().GetManifestResourceStream("PFClient.SampleRequest.xml"))
        using(var reader = new StreamReader(stream))
        {
            var payload = reader.ReadToEnd();
            string uploadResult = service.UploadFiling("TestRefId", "test@company.org", payload);
            Console.WriteLine(uploadResult);
        }
    }

    }

    /// <summary>
    /// Call FIP endpoint to get token
    /// </summary>
    /// <param name="userName"></param>

```

```

    /// <param name="password"></param>
    /// <returns></returns>
    private static FipResponse GetFipToken(string userName, string password) {
        //We used RestClient, but it can be any REST library of your choice
        var client = new RestClient
        {
            //IMPORTANT: Use basic authentication for call to FIP
            Authenticator = new HttpBasicAuthenticator(userName, password)
        };
        var request = new RestRequest(fipUrl);
        //This needs to be a POST call
        var task = client.PostAsync<FipResponse>(request);
        //Make the call synchronous
        return task.GetAwaiter().GetResult();
    }
}

```